
SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: GRAFFITI GONE
PRODUCT CODES: 2210

PRODUCT USE: Paint Remover

MANUFACTURER: QuestVapco Corporation
ADDRESS: PO Box 624
Brenham, TX 77834

EMERGENCY PHONE: 713-896-8188
CHEMTEL PHONE: 1-800-255-3924
OTHER CALLS: 713-896-8188

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Name</u>	<u>CAS NO.</u>	<u>PEL</u>	<u>TLV</u>
ACETONE	67-64-1	1000 PPM	750 PPM
XYLENE	1330-20-7	100 PPM	100 PPM
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Extremely Flammable Aerosol under pressure do not expose to high temperatures or store in direct sunlight.

ROUTES OF ENTRY: Inhalation, Skin (irritant, permeator), Ingestion

POTENTIAL HEALTH EFFECTS

EYES: Redness, irritation, causes temporary corneal opacity

SKIN: Severe irritation, Defatting of Skin

INGESTION: Nausea

INHALATION: Will cause dizziness, anesthesia and possibly death if breathed directly.

ACUTE HEALTH HAZARDS: See above

CHRONIC HEALTH HAZARDS: May cause damage to the following organs: blood, kidneys, liver, mucous membranes, bone marrow, central nervous system (CNS).

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: No

SECTION 4: FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention. **SKIN:** Wash with soap and water for 15 minutes. If irritation develops seek medical attention. **INGESTION:** Drink several glasses of water. Seek medical attention immediately. do not induce vomiting unless directed by medical authority. **INHALATION:** Move to fresh air. Administer artificial breathing if breathing has stopped. Seek immediate medical help.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR (% BY VOLUME): UPPER: unknown LOWER: unknown

FLASH POINT (Method TCC): F: 65 C: 19 **AUTOIGNITION TEMPERATURE:** F: N/A C: N/A

NFPA HAZARD CLASSIFICATION: HEALTH: 2 **FLAMMABILITY:** 3 **REACTIVITY:** 1 **OTHER:** N/A

HMIS HAZARD CLASSIFICATION: HEALTH: 2 **FLAMMABILITY:** 3 **REACTIVITY:** 1 **PROTECTION:** B

EXTINGUISHING MEDIA: ABC Fire extinguisher, Large warehouse fires recommend foam or water mist.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers and dilute spills to nonflammable mixture.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cans can burst with force under fire conditions

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Remove any source of ignition. Use non-sparking tools and equipment. Use absorbent on spill sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Do not use or store near heat, sparks, or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

VENTILATION: Use only in well ventilated areas. Forced ventilation required. Local exhaust preferred to general.

RESPIRATORY PROTECTION: Not required under normal use. If exposure levels are exceeded then organic vapor cartridge respirator or SCBA will be needed.

EYE PROTECTION: Safety glasses

SKIN PROTECTION: Solvent resistant gloves recommended

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Not Required

WORK HYGIENIC PRACTICES: Wash hands after use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Liquid

ODOR: Solvent

PHYSICAL STATE: Liquid under pressure

pH AS SUPPLIED: N/A

BOILING POINT: F: >150 C: >65.5

VAPOR PRESSURE (mmHg): 77.3 @ F: 77 C: 25

VAPOR DENSITY (AIR = 1): > 1 @ F: 77 C: 25

SPECIFIC GRAVITY (H₂O = 1): 0.87

EVAPORATION RATE (butyl acetate =1): > 1

SOLUBILITY IN WATER: 63%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Open flames, temperatures above 120F and Hot surfaces

INCOMPATIBILITY (MATERIAL TO AVOID): Concentrated nitric & sulfuric acid mixtures, oxidizing materials, chloroform, alkalis, chlorine compounds, acids, plastics, rubber, coatings.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Oxides of Carbon

HAZARDOUS POLYMERIZATION: NO

CONDITIONS TO AVOID (POLYMERIZATION):

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Acetone - 67-64-1 - ORAL (LD50): Acute: 5800 mg/kg [Rat]. 3000 mg/kg [Mouse]. 5340 mg/kg [Rabbit]. VAPOR (LC50): Acute: 50100 mg/m 8 hours [Rat]. 44000 mg/m 4 hours [Mouse].

Xylenes – 1330-20-7: Acute oral toxicity (LD50): 2119 mg/kg [Mouse], oral LD(50) 4300 mg/kg. Acute dermal toxicity (LD50): >1700 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 5000 4 hours [Rat].]. Detected in maternal milk in human. Passes through the placental barrier in animal. Embryotoxic and/or foetotoxic in animal. May cause adverse reproductive effects (male and female fertility (spontaneous abortion and fetotoxicity)) and birth defects based animal data.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Xylenes – 1330-20-7: The products of degradation are less toxic than the product itself.

Acetone, 67-64-1 - of this material is expected to readily biodegrade when released into the soil and is expected to evaporate quickly. It will also leach into the ground water and is expected to readily biodegrade. This material has a octanol-water partition coefficient of less than 3.0 and not expected to significantly bioaccumulate. Not expected to be toxic to aquatic life. The LC50/96-hour values for fish are over 100mg/L.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with local, State and Federal regulations. Do not puncture or incinerate container. Do not reuse empty container. Wrap container and place in trash collection.

RCRA HAZARD CLASS: Hazardous

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION

PROPER SHIPPING NAME: Consumer Commodity
HAZARD CLASS: ORM-D
ID NUMBER:
PACKING GROUP: N/A
LABEL STATEMENT:

WATER TRANSPORTATION

Refer to IMDG regulations

PROPER SHIPPING NAME: AEROSOLS IN LIMITED QUANTITIES OF CLASS 2
PRIMARY HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: 1950
Packing Group: None
NOTE: Page 2102

AIR TRANSPORTATION

Refer to IATA regulations

PROPER SHIPPING NAME: AEROSOLS IN LIMITED QUANTITIES OF CLASS 2
PRIMARY HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: 1950
Packing Group: None

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

TSCA (TOXIC SUBSTANCE CONTROL ACT): All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Xylenes: 100 lbs. (45.36 kg)

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT): Xylenes

311/312 HAZARD CATEGORIES: Flammable.

313 REPORTABLE INGREDIENTS: Xylenes - 1330-20-7 - 35% by weight

STATE REGULATIONS: Xylenes - 1330-20-7 - Connecticut hazardous material survey, Illinois chemical safety act, New York acutely hazardous substances, Rhode Island RTK hazardous substances, Pennsylvania RTK, Minnesota, Michigan critical material, Massachusetts RTK, Massachusetts spill list, New Jersey spill list, Louisiana spill reporting, California Director's List of Hazardous Substances.

INTERNATIONAL REGULATIONS: Xylenes – EINECS, WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2A: Material causing other toxic effects (VERY TOXIC). DSCL (EEC): R10- Flammable. R21- Harmful in contact with skin. R36/38- Irritating to eyes and skin. S2- Keep out of the reach of children. S36/37- Wear suitable protective clothing and gloves. S46- If swallowed, seek medical advice immediately and show this container or label.

SECTION 16: OTHER INFORMATION

PREPARATION BY: Juanita Mercure

DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However there is no assumption of any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this MSDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this MSDS shall be created or inferred by any statement in this MSDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.