

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 1/11
(30646775/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterSeal SL 1 gray

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: sealant

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Flam. Liq.	4	Flammable liquids
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Resp. Sens.	1	Respiratory sensitization
Skin Sens.	1	Skin sensitization
Carc.	2	Carcinogenicity
Repr.	2 (unborn child)	Reproductive toxicity
STOT RE	1	Specific target organ toxicity — repeated exposure

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 2/11
(30646775/SDS_GEN_US/EN)

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H227	Combustible liquid.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H361	Suspected of damaging the unborn child.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P260	Do not breathe dust/gas/mist/vapours.
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P202	Do not handle until all safety precautions have been read and understood.
P284	In case of inadequate ventilation wear respiratory protection.
P270	Do not eat, drink or smoke when using this product.
P264	Wash with plenty of water and soap thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314	Get medical advice/attention if you feel unwell.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P303 + P362	IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364	Take off contaminated clothing and wash before reuse.
P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician.
P370 + P378	In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.

Precautionary Statements (Storage):

P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 3/11
(30646775/SDS_GEN_US/EN)

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Labeling of special preparations (GHS):

SENSITIZATION CAN OCCUR IN SOME INDIVIDUALS, LEADING TO ASTHMA-LIKE SPASMS OF THE BRONCHIAL TUBES AND DIFFICULTY BREATHING. INDIVIDUALS WITH A HISTORY OF RESPIRATORY ILLNESS, ASTHMATIC CONDITIONS, EYE DAMAGE OR TDI SENSITIZATION SHOULD NOT BE EXPOSED TO THIS PRODUCT. TDI IS INCLUDED IN THE NTP ANNUAL REPORT ON CARCINOGENS. RESULTS FROM A TDI HEALTH STUDY INDICATE THAT OVEREXPOSURE TO A RESPIRATORY IRRITANT, RESULTING IN LOWER RESPIRATORY TRACT SYMPTOMS COULD INCREASE THE RISKS OF DEVELOPING ASTHMA-LIKE REACTIONS FROM SUBSEQUENT TDI EXPOSURE.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
1317-65-3	> 25.0 - < 50.0%	Limestone
13463-67-7	>= 3.0 - < 5.0%	Titanium dioxide
1305-78-8	>= 1.0 - < 3.0%	calcium oxide
8052-41-3	>= 1.0 - < 3.0%	Stoddard solvent
91-08-7	>= 0.3 - < 1.0%	toluene-2,6-diisocyanate
2530-83-8	>= 0.2 - < 0.3%	trimethoxy(3-(oxiranylmethoxy)propyl)silane
4083-64-1	>= 0.1 - < 0.2%	4-toluenesulphonyl isocyanate
1333-86-4	>= 0.1 - < 0.2%	carbon black
149-57-5	> 0.0 - < 0.1%	2-ethylhexanoic acid

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 4/11
(30646775/SDS_GEN_US/EN)

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Eye irritation, skin irritation, allergic symptoms
Hazards: Symptoms can appear later.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.
For large amounts: Pump off product.

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 5/11
(30646775/SDS_GEN_US/EN)

7. Handling and Storage

Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

toluene-2,6-diisocyanate	ACGIH TLV	TWA value 0.005 ppm ; STEL value 0.02 ppm ;
2-ethylhexanoic acid	ACGIH TLV	TWA value 5 mg/m3 Inhalable fraction and vapor ;
calcium oxide	OSHA PEL ACGIH TLV	PEL 5 mg/m3 ; TWA value 5 mg/m3 ; TWA value 2 mg/m3 ;
Limestone	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
carbon black	OSHA PEL ACGIH TLV	PEL 3.5 mg/m3 ; TWA value 3.5 mg/m3 ; TWA value 3.5 mg/m3 ; TWA value 3 mg/m3 Inhalable fraction ;
Titanium dioxide	OSHA PEL ACGIH TLV	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ; TWA value 10 mg/m3 ;
Stoddard solvent	OSHA PEL ACGIH TLV	PEL 500 ppm 2,900 mg/m3 ; TWA value 100 ppm ;

Advice on system design:

Provide adequate exhaust ventilation to control work place concentrations.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 6/11
(30646775/SDS_GEN_US/EN)

Eye protection:

Safety glasses with side-shields.

Body protection:

Impermeable protective clothing

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Odour:	mild	
Odour threshold:	No applicable information available.	
Colour:	grey	
pH value:	No applicable information available.	
Melting point:	No applicable information available.	
Boiling point:	No applicable information available.	
Sublimation point:	No applicable information available.	
Flash point:	approx. 85.00 °C	(ASTM D3278, closed cup)
Flammability:	No applicable information available.	
Lower explosion limit:	No applicable information available.	
Upper explosion limit:	No applicable information available.	
Autoignition:	No applicable information available.	
Vapour pressure:	No applicable information available.	
Density:	approx. 1.3200 g/cm ³ (25.00 °C)	
Relative density:	No applicable information available.	
Vapour density:	No applicable information available.	
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	No applicable information available.	
Viscosity, kinematic:	No applicable information available.	
Solubility in water:	No applicable information available.	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Evaporation rate:	No applicable information available.	
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 7/11
(30646775/SDS_GEN_US/EN)

Not an oxidizer.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Inhalation of diisocyanates may cause irritation of the mucous membranes of the nose, throat or trachea, breathlessness, chest discomfort, difficult breathing and reduced pulmonary function. High airborne concentrations may result additionally in eye irritation, headache, chemical bronchitis, asthma-like symptoms or pulmonary edema. Isocyanates have also been reported to cause hyper-sensitivity pneumonitis, which is characterized by flu-like symptoms, the onset of which may be delayed. Symptoms include nausea, vomiting and abdominal pain.

Oral

No applicable information available.

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation.

Sensitization

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 8/11
(30646775/SDS_GEN_US/EN)

Assessment of sensitization: Sensitization after skin contact possible. The substance may cause sensitization of the respiratory tract.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Prolonged exposure may cause chronic effects.

Genetic toxicity

Assessment of mutagenicity: The substance was mutagenic in various bacterial test systems; however, a mutagenic effect could not be confirmed in mammalian cell culture.

Carcinogenicity

Assessment of carcinogenicity: Contains a compound classified as IARC Group 2B (possibly carcinogenic to humans).

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Information on: toluene-2,6-diisocyanate

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Information on: carbon black

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was observed. A clear indication of an increased risk of cancer in humans has so far not been shown. No carcinogenic potential can be deduced from other studies with rats and mice.

Reproductive toxicity

Assessment of reproduction toxicity: The results of animal studies gave no indication of a fertility impairing effect.

Information on: 2-ethylhexanoic acid

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect.

Teratogenicity

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 9/11
(30646775/SDS_GEN_US/EN)

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Eye irritation, skin irritation, allergic symptoms

Medical conditions aggravated by overexposure

The isocyanate component is a respiratory sensitizer. It may cause allergic reaction leading to asthma-like spasms of the bronchial tubes and difficulty in breathing. Medical supervision of all employees who handle or come into contact with isocyanates is recommended. Contact may aggravate pulmonary disorders. Persons with history of respiratory disease or hypersensitivity should not be exposed to this product. Preemployment and periodic medical examinations with respiratory function tests (FEV, FVC as a minimum) are suggested. Persons with asthmatic conditions, chronic bronchitis, other chronic respiratory diseases, recurrent eczema or pulmonary sensitization should be excluded from working with isocyanates. Once a person is diagnosed as having pulmonary sensitization (allergic asthma) to isocyanates, further exposure is not recommended.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Based on available Data, the classification criteria are not met.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Poorly biodegradable.

The product is unstable in water. The elimination data also refer to products of hydrolysis.

Assessment biodegradation and elimination (H2O)

Information on: TDI

Poorly biodegradable. The product is unstable in water. The elimination data also refer to products of hydrolysis.

Mobility in soil

Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 10/11
(30646775/SDS_GEN_US/EN)

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

USDOT

Classified as combustible liquid in containers greater than 119 gallons.

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

TSCA § 5 proposed Significant New Use Restriction (SNUR)

listed on TSCA-Inventory with S-flag

This product contains a substance subject to a pending SNUR.

40 CFR 721.10789

EPCRA 311/312 (Hazard categories): Acute; Chronic

EPCRA 313:

CAS Number

91-08-7

Chemical name

toluene-2,6-diisocyanate

CERCLA RQ

1000 LBS

100 LBS

CAS Number

108-88-3

108-90-7; 584-84-9; 91-08-7

Chemical name

Toluene

chlorobenzene; toluene-2,4-diisocyanate; toluene-2,6-diisocyanate

State regulations

State RTK

NJ

CAS Number

1305-78-8

1317-65-3

13463-67-7

8052-41-3

91-08-7

1333-86-4

PA

1305-78-8

1317-65-3

Chemical name

calcium oxide

Limestone

Titanium dioxide

Stoddard solvent

toluene-2,6-diisocyanate

carbon black

calcium oxide

Limestone

Safety Data Sheet

MasterSeal SL 1 gray

Revision date : 2015/07/15
Version: 2.0

Page: 11/11
(30646775/SDS_GEN_US/EN)

13463-67-7	Titanium dioxide
28553-12-0	Di-isononylphthalate
8052-41-3	Stoddard solvent

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health : 2 Fire: 1 Reactivity: 1 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2015/07/15

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET