


# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

<b>SECTION 1: Identification of the substance/mixture and of the company/undertaking</b>	
<b>1.1 Product Identifier</b>	
Product form	Mixture
Trade Name	STIC-O-STEEL POW-R Putty – 2 oz / 4 oz Grey
Product Code	SS2, SS4
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b>	
Use of the substance	Multiple Use Epoxy Putty
<b>1.3 Details of the supplier of the safety data sheet</b>	
Access-Able Technologies Inc	
1275 Bennett Drive Suite 115	
Longwood, FL 32750	
T 800-572-4894	
<b>1.4 Emergency telephone number</b>	
Emergency number	CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 Intl
<b>SECTION 2: Hazards identification</b>	
<b>2.1 Classification of the substance or mixture</b>	
<b>Classification (GHS-US)</b>	
Carc. 1A H350	
Full text of H-phrases: see section 16	
<b>2.2 Label elements</b>	
<b>GHS-US labeling</b>	
Hazard pictograms (GHS-US)	 GHS08
Signal word (GHS-US)	Danger
Hazard statements (GHS-US)	H350 – May cause cancer
Precautionary statements	P201 – Obtain special instructions
	P202 – Do not handle until all safety precautions have been read and understood
	P280 – Wear protective gloves, protective clothing, eye protection, face protection
	P308 + P313 – If exposed or concerned: Get medical advice/attention
	P405 – Store locked up
	P501 – Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations
<b>2.3 Other hazards</b>	
Other hazards not contributing to the classification	None under normal conditions
<b>2.4 Unknown acute toxicity (GHS-US)</b>	
No data available	

# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

<b>SECTION 3: Composition/information on ingredients</b>			
<b>3.1 Substance</b>			
Not applicable			
<b>3.2 Mixture</b>			
<b>Name</b>	<b>Product identifier</b>	<b>%</b>	<b>Classification (GHS-US)</b>
Talc	(Cas No) 14807-96-6	39.954 -66.59	Not Classified
2,2-bis-[4-(2,3-epoxypropoxy)propane, polymer	(Cas No) 25085-99-8	10 – 30	Not Classified
GMP-800	(Cas No) Trade Secret	10 – 30	Not Classified
Dolomite	(Cas No) 16389-88-1	3.3295 – 6.659	Not Classified
Magnesium carbonate	(Cas No) 546-93-0	0.6659 – 3.3295	Not Classified
Quartz	(Cas No) 14808-60-7	0.6659 – 3.3295	Acute Tox. 4 (Oral), H302 Carc. 1A, H350
2,4,6-tris(dimethylaminomethyl)phenol	(Cas No) 90-72-2	> 1.5675	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315
Electronic grade resin	(Cas No) 28064-14-4	1 – 5	Not Classified
Iron(III) oxide	(Cas No) 1309-37-1	1 – 5	Not Classified
Epoxy White	(Cas No) 025085-99-8	< 1	Not Classified
Dmp-30		< 0.0825	Not Classified
Carbon black	(Cas No) 1333-86-4	< 0.0389702	Carc. 2, H351
Silicon, crystalline	(Cas No) 7440-21-3	< 0.0186	Not Classified
Chromium	(Cas No) 7440-47-3	< 0.0124	Not Classified
Manganese	(Cas No) 7439-96-5	< 0.01178	Not Classified

<b>SECTION 4: First aid measures</b>	
<b>4.1 Description of first aid measures</b>	
First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
<b>4.2 Most important symptoms and effects, both acute and delayed</b>	
Symptoms/injuries	Not expected to present a significant hazard under anticipated conditions of normal use. If you feel unwell, seek medical advice.
Symptoms/injuries after inhalation	May cause cancer by inhalation
Symptoms/injuries after skin contact	May cause slight irritation
Symptoms/injuries after eye contact	May cause slight eye irritation

# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

Symptoms/injuries after ingestion	May be harmful if swallowed and enters airways
<b>4.3 Indication of any immediate medical attention and special treatment needed</b>	
No additional information available	

<b>SECTION 5: Firefighting measures</b>	
<b>5.1 Extinguishing media</b>	
Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand
Unsuitable extinguishing media	Do not use a heavy water stream.
<b>5.2 Special hazards arising from the substance or mixture</b>	
No additional information available	
<b>5.3 Advice for firefighters</b>	
Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.

<b>SECTION 6: Accidental release measures</b>	
<b>6.1 Personal precautions, protective equipment and emergency procedures</b>	
General measures	Remove ignition sources
<b>6.1.1. For non-emergency personnel</b>	
Protective equipment	Safety glasses. Gloves
Emergency procedures	Evacuate unnecessary personnel.
<b>6.1.2. For emergency responders</b>	
Protective equipment	Equip cleanup crew with proper protection
Emergency procedures	Ventilate area.
<b>6.2 Environmental precautions</b>	
Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters	
<b>6.3 Methods and material for containment and cleaning up</b>	
For containment	Keep in tubing if not used
Methods for cleaning up	On land, sweep or shovel into suitable containers. Minimize generation of dust. Store away from other materials
<b>6.4 Reference to other sections</b>	
See Heading 8. Exposure controls and personal protection.	

<b>SECTION 7: Handling and storage</b>	
<b>7.1 Precautions for safe handling</b>	
Precautions for safe handling	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions. Do not handle until all safety precautions have been read and understood.
Hygiene measures	Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Wash

# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet



According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

	hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
<b>7.2 Conditions for safe storage, including any incompatibilities</b>	
Technical measures	Comply with applicable regulations.
Storage conditions	Keep only in the original container in a cool, well ventilated place away from: Keep container closed when not in use
Incompatible products	Strong bases, strong acids
Incompatible materials	Sources of ignition. Direct sunlight
<b>7.3 Specific end use(s)</b>	
Follow Label Directions.	

### SECTION 8: Exposure controls/personal protection

<b>8.1 Control parameters</b>		
<b>Carbon black (1333-86-4)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
<b>Iron(III) oxide (1309-37-1)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
<b>Manganese (7439-96-5)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
<b>Chromium (7440-47-3)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.5 mg/m <sup>3</sup>
<b>Talc (14807-96-6)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Dolomite (16389-88-1)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
<b>Magnesium carbonate (546-93-0)</b>		
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
<b>Quartz (14808-60-7)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	.01 mg/m <sup>3</sup>
<b>8.2 Exposure controls</b>		
Appropriate engineering controls	Local exhaust ventilation, vent hoods.	
Personal protective equipment	Avoid all unnecessary exposure. Gloves. Safety glasses.	
		
Hand protection	Wear protective gloves.	
Eye protection	Chemical goggles or safety glasses.	

# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

Skin and body protection	Wear suitable protective clothing.
Respiratory protection	Wear appropriate mask.
Other information	Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	Solid
Appearance	Cylindrical putty stick
Color	Gray
Odor	Pungent
Odor threshold	No data available
pH	No data available
Relative evaporation rate (butyl acetate=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	> 100 °C
Flash point	> 100 °C
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	No data available
Vapor pressure	No data available
Relative vapor density at 20 °C	No data available
Relative density	1.7
Solubility	No data available
Log Pow	No data available
Log Kow	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	No data available
Explosive properties	No data available
Oxidizing properties	No data available
Explosive limits	No data available

#### 9.2 Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No additional information available

#### 10.2 Chemical stability

Not established

#### 10.3 Possibility of hazardous reactions

Not established

#### 10.4 Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

<b>10.5 Incompatible materials</b>
Strong acids. Strong bases.
<b>10.6 Hazardous decomposition products</b>
Toxic fume. Carbon monoxide. Carbon dioxide

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Acute toxicity	Not classified
<b>GMP-80 (Trade Secret)</b>	
LD50 oral rat	2.6 g/kg
LD50 dermal rabbit	> 10.2 g/kg
<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
LD50 oral rat	1200 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)
<b>Carbon black (1333-86-4)</b>	
LD50 oral rat	> 8000 mg/kg (Rat; OECD 401; Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit)
<b>2,2-bis-[4-(2,3-epoxypropoxy)phenyl]propane, polymer (25085-99-8)</b>	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 20000 mg/kg (Rabbit)
<b>Electronic grade resin (28064-14-4)</b>	
LD50 oral rat	4000 mg/kg
<b>Iron(III) oxide (1309-37-1)</b>	
LD50 oral rat	> 5000 mg/kg (Rat; Literature study)
<b>Manganese (7439-96-5)</b>	
LD50 oral rat	9000 mg/kg (Rat)
<b>Silicon, crystalline (7440-21-3)</b>	
LD50 oral rat	> 3160 mg/kg (Rat; OECD 401:Acute Oral Toxicity; Experimental value; > 5000 mg/kg bodyweight; Rat Weight of evidence)
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Weight of evidence)
<b>Quartz (14808-60-7)</b>	
LD50 oral rat	500 mg/kg
Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Not classified
Respiratory or skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	May cause cancer.
<b>Carbon black (1333-86-4)</b>	
IARC group	2B
<b>Iron(III) oxide (1309-37-1)</b>	
IARC group	3

# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

<b>Chromium (7440-47-3)</b>	
IARC group	3
<b>Talc (14807-96-6)</b>	
IARC group	3
<b>Quartz (14808-60-7)</b>	
IARC group	1
Reproductive toxicity	Not classified
Specific target organ toxicity(single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	May cause cancer by inhalation
Symptoms/injuries after skin contact	May cause slight irritation
Symptoms/injuries after eye contact	May cause slight eye irritation
Symptoms/injuries after ingestion	May be harmful if swallowed and enters airway

<b>SECTION 12: Ecological information</b>	
<b>12.1 Toxicity</b>	
<b>GMP-80 (Trade Secret)</b>	
LC50 fish 1	> 100 mg/l
<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
LC50 fish 1	> 100 mg/l (96 h; Pisces; Nominal concentration)
EC50 Daphnia 1	10 – 100 mg/l (Invertebrate; Estimated value)
LC50 fish 2	70.9 mg/l (96 h; Pisces)
Threshold limit algae 1	10 – 100, Algae
Threshold limit algae 2	84 mg/l (72 h; Scenedesmus subspicatus; Growth rate)
<b>Dmp-30</b>	
LC50 fish 1	175 mg/l (96 h; Cyprinus carpio; fresh water)
LC50 other aquatic organisms 1	750 – 1000 mg/l (96 h; Brachyura; Fresh water)
LC50 fish 2	180 – 240 mg/l (96 h; Salmo Gairdneri / oncorhynchus mykiss; Fresh water)
LC50 other aquatic organisms 2	718 mg/l (96 h; Palaemonetes SP; Fresh water)
<b>Carbon black (1333-86-4)</b>	
LC50 fish 1	> 1000 mg/l (96 h; Brachydanio rerio)
EC50 Daphnia 1	> 5600 mg/l (24 h; Daphnia magna)
<b>2,2-bis-[4-(2,3-epoxypropoxy)phenyl]propane, polymer (25085-99-8)</b>	
LC50 fish 1	3.1 mg/l (96 h; Freshwater fish; Pimephales promelas)
EC50 Daphnia 1	1.4 mg/l (48 h)
<b>Iron(III) oxide (1309-37-1)</b>	
LC50 fish 1	> 1000 mg/l (48 h; Leuciscus idus; Nominal concentration)

# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

<b>Talc (14807-96-6)</b>	
LC50 fish 1	> 100 g/l (24 h; Brachydanio rerio; Intermittent flow)
<b>12.2 Persistence and degradability</b>	
<b>STIC-O-STEEL – 2 oz and 4 oz Grey Putty</b>	
Persistence and degradability	Not established
<b>GMP-80 (Trade Secret)</b>	
Persistence and degradability	Not established
<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
Persistence and degradability	Not readily biodegradable in water. Highly mobile in soil. Low potential for absorption in soil.
<b>Dmp-30</b>	
Persistence and degradability	Biodegradability in soil; no data available
<b>Carbon black (1333-86-4)</b>	
Persistence and degradability	Biodegradability: not applicable. Biodegradability in soil: not applicable. Absorbs into the soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>2,2-bis-[4-(2,3-epoxypropoxy)phenyl]propane, polymer (25085-99-8)</b>	
Persistence and degradability	Not established
<b>Electronic grade resin (28064-14-4)</b>	
Persistence and degradability	Biodegradability in soil: no data available
<b>Epoxy white (025085-99-8)</b>	
Persistence and degradability	Not established
<b>Iron(III) oxide (1309-37-1)</b>	
Persistence and degradability	Biodegradability: not applicable. Adsorbs into the soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>Manganese (7439-96-5)</b>	
Persistence and degradability	Biodegradability: not applicable. Adsorbs into the soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>Silicon, crystalline (7440-21-3)</b>	
Persistence and degradability	Not established
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable



# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

<b>Chromium (7440-47-3)</b>	
Persistence and degradability	Biodegradability: not applicable. Biodegradability in soil: not applicable. Adsorbs into the soil
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>Talc (14807-96-6)</b>	
Persistence and degradability	Biodegradability: not applicable
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>Dolomite (16389-88-1)</b>	
Persistence and degradability	Biodegradability: not applicable
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>Magnesium carbonate (546-93-0)</b>	
Persistence and degradability	Biodegradability: not applicable
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>Quartz (14808-60-7)</b>	
Persistence and degradability	Biodegradability: not applicable
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>12.3 Bioaccumulative potential</b>	
<b>STIC-O-STEEL – 2 oz and 4 oz Grey Putty</b>	
Bioaccumulative potential	Not established
<b>GMP-80 (Trade Secret)</b>	
Bioaccumulative potential	Not established
<b>2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)</b>	
Log Pow	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Dmp-30</b>	
Bioaccumulative potential	No bioaccumulation data available

# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

<b>Carbon black (1333-86-4)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>2,2-bis-[4-(2,3-epoxypropoxy)phenyl]propane, polymer (25085-99-8)</b>	
Bioaccumulative potential	Not established
<b>Electronic grade resin (28064-14-4)</b>	
Bioaccumulative potential	No bioaccumulation data available
<b>Epoxy white (025085-99-8)</b>	
Bioaccumulative potential	Not established
<b>Iron(III) oxide (1309-37-1)</b>	
Bioaccumulative potential	No bioaccumulation data available
<b>Manganese (7439-96-5)</b>	
BCF fish 1	81 (Pisces)
BCF other aquatic organisms 1	300000 (Mollusca)
BCF other aquatic organisms 2	125000 (Crustacea)
Bioaccumulative potential	Not established
<b>Silicon, crystalline (7440-21-3)</b>	
Bioaccumulative potential	Not established
<b>Chromium (7440-47-3)</b>	
BCF fish 1	0.0048 (Pisces; Dry weight)
BCF other aquatic organisms 1	0.443 (Lamellibranchiata; Dry weight)
Bioaccumulative potential	Bioaccumable.
<b>Talc (14807-96-6)</b>	
Bioaccumulative potential	Not established
<b>Dolomite (16389-88-1)</b>	
Bioaccumulative potential	No bioaccumulation data available
<b>Magnesium carbonate (546-93-0)</b>	
Bioaccumulative potential	No bioaccumulation data available
<b>Quartz (14808-60-7)</b>	
Log Pow	Not applicable
Bioaccumulative potential	No bioaccumulation data available
<b>12.4 Mobility in soil</b>	
<b>Carbon black (1333-86-4)</b>	
Ecology – soil	Not toxic to plants. Not toxic to animals.
<b>Silicon, crystalline (7440-21-3)</b>	
Surface tension	0.74 N/m (1410 °C)
<b>12.5 Other adverse effects</b>	
Other information	Avoid release to the environment
<b>SECTION 13: Disposal considerations</b>	
<b>13.1 Waste treatment methods</b>	
Waste disposal recommendations	Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations

# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

Ecology – waste materials	Avoid release to the environment
---------------------------	----------------------------------

<b>SECTION 14: Transport information</b>	
In accordance with ADR / RID / IMDG / IATA / ADN	
US DOT (ground)	Not Regulated
ICAO/IATA (air)	Not Regulated
IMO/IMDG (water)	Not Regulated
<b>14.2 UN proper shipping name</b>	
Proper Shipping Name (DOT)	Not Regulated
<b>14.3 Additional information</b>	
Other information	No supplementary information available
<b>Overland Transport</b>	
No additional information available	
<b>Transport by sea</b>	
No additional information available	
<b>Air transport</b>	
No additional information available	

<b>SECTION 15: Regulatory information</b>	
<b>15.1 US Federal regulations</b>	
<b>STIC-O-STEEL – 2 oz and 4 oz Grey Putty</b>	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
<b>GMP-80 (Trade Secret)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>2,2-bis-[4-(2,3-epoxypropoxy)phenyl]propane, polymer (25085-99-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
<b>Electronic grade resin (28064-14-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
<b>Epoxy white (025085-99-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>15.2 International regulations</b>	
<b>Canada</b>	
<b>GMP-80 (Trade Secret)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>2,2-bis-[4-(2,3-epoxypropoxy)phenyl]propane, polymer (25085-99-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B – Toxic material causing other toxic effects
<b>Electronic grade resin (28064-14-4)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B – Toxic material causing other toxic effects

# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

<b>EU-Regulations</b>	
<b>GMP-80 (Trade Secret)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
<b>2,2-bis-[4-(2,3-epoxypropoxy)phenyl]propane, polymer (25085-99-8)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
<b>Electronic grade resin (28064-14-4)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	
Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]	
Carc. Cat 1; R49	
R43	
R52/53	
Full text of R-Phrases: see section 16	
<b>15.2.2 National regulations</b>	
<b>GMP-80 (Trade Secret)</b>	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	
Listed on AICS (Australian Inventory of Chemical Substances)	
Listed on Korean ECL (Existing Chemical List)	
<b>2,2-bis-[4-(2,3-epoxypropoxy)phenyl]propane, polymer (25085-99-8)</b>	
Listed on AICS (Australian Inventory of Chemical Substances)	
Listed on KECI (Korean Existing Chemicals Inventory)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	
Listed on the Japanese ENCS (Existing & New Chemical Substances) Inventory	
Listed on NZIoC (New Zealand Inventory of Chemicals)	
<b>Electronic grade resin (28064-14-4)</b>	
Listed on the Korean ECL (Existing Chemicals List)	
Listed on the Japanese ENCS (Existing & New Chemical Substances) Inventory	
Listed on AICS (Australian Inventory of Chemical Substances)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	
Listed on NZIoC (New Zealand Inventory of Chemicals)	
<b>15.3 US State regulations</b>	
<b>No additional information available</b>	

<b>SECTION 16: Other information</b>	
Other information	None
Full text of H-Phrases: see section 16	
Acute Tox. 4 (Oral)	Acute Toxicity (oral) Category 4
Carc. 1A	Carcinogenicity Category 1A
Carc. 2	Carcinogenicity Category 2
Skin Irrit. 2	Skin Corrosion/irritation Category 2


# STIC-O-STEEL - 2 oz and 4 oz Grey

## Safety Data Sheet

According to Federal Register / Vol 77, No. 58 / Monday 26, 2012 / Rules and Regulations

Revision Date: 6/24/2015

Version: 01

H302	Harmful if swallowed
H315	Causes skin irritation
H350	May cause cancer
H351	Suspected of causing cancer
	
NFPA Health Hazard	1 –Exposure could cause irritation but only minor residual injury even if no treatment is given
NFPA Fire Hazard	0 –Materials that will not burn
NFPA Reactivity	0 – Normally stable, even under fire exposure conditions, and are not reactive with water.
<b>HMIS III Rating</b>	
Health	1 Slight Hazard – Irritation or minor reversible injury possible
Flammability	0 Minimal Hazard
Physical	0 Minimal Hazard
Personal Protection	B

### SDS US (GHS HazCom 2012) – Access-Able Technologies Inc

*The Supplier identified in Section 1 of this SDS has evaluated and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product.*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/Distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of this data. No warranty against infringement of any patent, copyright or trademark is made or implied.*