MATERIAL SAFETY DATA SHEET comply with OSHA's Hazard		
PRODUCT NUMBER: 655 IDENTITY: EZ WIPES WBOARD	CLEANER	Revision Date: 10/07/2004
Section I		
HOUSTON	M 529 ODS INDUSTRIAL PARK	Telephone Numbers: Emergency: 800/255-3924 Information: 713/8968188
HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 4 HEALTH: 2 PERSONAL PROTECT: G Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)		
Name	Cas No. OSHA PE	L ACGIH TLV OTHER LIM %
LINEAR ALCOHOL ETHOXYLATE	34398-01-1 NA	NA NA

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: >150F Specific Gravity (water=1) 0.70 Vapor Pressure(mm Hg) 110PSI Melting Point:
Vapor Density(AIR=1) >1 Evaporation Rate
Solubility in Water: N/A (Butyl Acetate=1 N/AEvaporation Rate: <1

(Butyl Acetate=1) Appearance and Odor: COLORLESS LIQUID, ETHER ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

______ Flash Point(Method Used):<0 TCC Flammable Limits: LEL:1.0 UEL: 36.0

Extinguishing Media: DRY CHEMICAL, ALCOHOL FOAM OR CO2 Special Fire Fighting Procedures: COOL SURROUNDING CONTAINERS WITH WATER FOG. WEAR SELF CONTAINED BREATHING APPRATUS (SCBA). SHUT OFF ALL SOURCES OF IGNITION. USE WATER SPRAY TO DISPERSE VAPORS AND PROTECT PERSONNEL. Unusual Fire and Explosion Hazards: WEAR SCBA WITH FULL FACE SHIELD. VAPORS ARE HEAVIER THAN AIR AND MAY ACCUMULATE IN LOW AREAS OR ALONG THE GROUND. ELIMINATE ALL SOURCES OF IGNITION. CARBON OXIDES FORMED WHEN BURNED.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 655

Stability: Unstable: Conditions to avoid: DO NOT STORE IN DIRECT Stable: X SUNLIGHT. AVOID TEMPERATURES ABOVE 120 F

Incompatability (Materials to Avoid): STRONG OXIDIZERS, SELECTED AMINES

STRONG ACIDS OR BASES

Hazardous Decomposition or Byproducts: CARBON OXIDES CAN FORM ON INCOMPLETE

COMBUSTION

Hazardous Polymerization: May Occur: Will Not Occur: X

Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: Y Skin: Y Ingestion: Y

Health Hazards (Acute and Chronic):

EYES: MAY CAUSE HEADACHES. SKIN: MAY CAUSE IRRITATION. INHALATION: MAY

CAUSE DIZZINESS OR UNCONSCIOUSNESS. INGESTION: MAY CAUSE NAUSEA.

Carcinogenicity: NTP:NO IARC Monographs:NO

Signs and Symptoms of Exposure: SEE ABOVE

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING. CONSULT PHYSICIAN FOR ANY OF THE ABOVE EXPOSURES.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

______ Steps to be Taken in Case Material is Released or Spilled: WEAR SCBA AND PROPER PROTECTIVE EQUIPMENT. SHUT OFF ALL SOURCES OF IGNITION AND DIKE AREA OF SPILL. KEEP OUT OF WATER SOURCES. CLEAN SPILL USING ABSORBENT MATERIAL. TRANSFER TO DOT APPROVED CONTAINER USING NON-SPARKING TOOLS. Waste Disposal Method: DISPOSE OF WASTE MATERIAL IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. DO NOT DISCARD IN TRASH COMPACTOR.

Precautions to be Taken in Handling and Storing: DO NOT DROP, REUSE OR REFILL CONTAINER. DO NOT STORE IN DIRECT SUNLIGHT. DO NOT EXPOSE TO HEAT, SPARKS, OPEN FLAME OR TEMPERATURES ABOVE 120 F. DO NOT INTENTIONALLY DILUTE Other Precautions: OR INHALE. SPRAY WITH ARROW POINT FACING AWAY FROM BODY. WEAR PROTECTIVE EQUIPMENT SUCH AS SPLASH GOGGLES.

Section VIII: CONTROL MEASURES

Respiratory Protection: NIOSH APPROVED SCBA OR ORGANIC VAPOR CHEMICAL

Ventilation: Local Exhaust: TO MAINTAIN CONCENTRATION BELOW TLV'S IN SECTION

Mechanical: N/A Special: N/A

Other: N/A

Protective Gloves: BUTYL GLOVES

Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.

Other Protective Clothing or Equipment:

NEOPRENE APRONS & CHEMICALLY RESISTANT BOOTS-AVOID SKIN & CLOTHING CONTACT

Work/Hygienic Practices:

GOOD PERSONNEL HYGIENE